



EzVIEW 23mm RGB Color Display

An EzView electronic message center from Entech is more than just a sign—it's a total advertising solution! Combined with our exclusive Ooh!Media 2009™ programming software EzView captures today's customer where it really matters—out, about, and ready to buy!

Efficient Digital Design at a Price Point Breakthrough

Whether you're upgrading from an older unit or are completely new to digital EMCs, you'll be impressed by the image quality, reliability, and amazing value of Entech's EzView color display. A dazzling array of millions of colors, along with an embedded controller, wired or wireless connectivity and intuitive Ooh!Media™ content creation and scheduling software make it easy to achieve that "WOW" factor for owners as well as for the passing public.

Maintenance Free

Entech's patented Protector™ case totally seals sensitive electronics from damage caused by environmental contaminants, corrosion, rain, dust, and salt fog. Efficient components and self-cooling design eliminate the need for venting, filters, or mechanical cooling devices. EzView runs cool, runs green, and runs longer, resulting in lower power bills, and, with no filters to change or vents to unclog, lower maintenance costs.

Lets you promote what you want, when you want it!

Standard Features

- Made in the USA: Fast order-to-delivery time!
- Available in the most popular sizes, from 1' X 4' to 5' X 13'
- EzView's new design concept simplifies electronics, reducing total part count and minimizing downtime.
- Standard Five Year Peace-of-Mind Warranty
- 15 fps display processing for dynamic messaging and eye-catching animations.
- Optional accessories include external temp and light sensors and wireless communications kit.

EzView 23mm Full Color LED Digital Display Specifications

			WIDTH OF DISPLAY IN FEET & INCHES AND NUMBER OF COLUMNS							
			3' 7.6"	4' 10.2"	7' 3.4"	8' 5.9"	9' 8.3"	10' 10.8"	12' 1.3"	13' 3.8"
			48	64	96	112	128	144	160	176
HEIGHT OF DISPLAY IN FEET & INCHES AND NUMBER OF ROWS	1' 2.9"	16			3.9 113 lbs	4.5 132 lbs	5.0 150 lbs	5.8 169 lbs	6.4 188 lbs	7.0 207 lbs
	2' 5.4"	32	3.9 99 lbs	5.0 132 lbs	7.8 198 lbs	8.9 231 lbs	10.0 264 lbs	11.6 297 lbs	12.8 330 lbs	13.9 363 lbs
	3' 7.9"	48		7.5 198 lbs	11.6 270 lbs	13.3 315 lbs	15.0 360 lbs	17.4 405 lbs	19.1 450 lbs	20.8 495 lbs
	4' 10.4"	64		10.0 240 lbs	15.5 360 lbs	17.7 420 lbs	20.0 480 lbs	23.2 540 lbs	25.5 600 lbs	27.7 660 lbs
TOTAL AC CURRENT (AMPS) /115VAC (TOTAL)										
WEIGHT OF UNIT										

NOTE Approximate dimensions , power and weight. Due to continuing product innovations, all specifications are subject to change without notice.

Pitch & Model Series	23mm / 0.9 inch pixel pitch 1 Red / 1 Green / 1 Blue LED per pixel
LED Color Capability	Gamma corrected, 16.7 million colors
Case	UL50 type 3R , IP24 aluminum cabinet; 9.7" deep
Viewability & Intensity	110° horizontal/40° vertical; calibrated to 5,000 nits
Programming	Operates with Ooh!Media 2009 content management software (purchased separately)
Controller	Embedded controller, 1GB FLASH, 32MB RAM, ARM9 processor
Connectivity to Controller	Wired Ethernet with optional Wireless (2.4GHz)
Service Access	Front-serviceable components. Power, Ethernet, and back-to-back connections through rear service panel.
Mounting	Mounting hardware included .
Dimming Feature	Programmable dimming with optional automatic photocell dimming
Graphics Frame Rate	15 fps
Graphics Capability	30 Minutes total runtime

Special Features	<ul style="list-style-type: none"> Our exclusive Protector™ case design seals out external contamination by rain, salt fog or dust, reflects solar radiation, and requires no filters. Automatic thermal protection for all electronics Thermostatically controlled fans for internal cooling Conformal coating on LED electronics Supports master/slave dual face display Optional accessories: wireless communications kit, external temperature and light sensor probe kit , back -to-back communications kit
Temperature:	-22° to 122°F / -30° to 50°C
Limited Warranty:	Five Year limited factory depot warranty. Third party supplied devices such as modems or wireless devices carry a warranty respective of the supplier. See ENTECH'S Terms & Conditions for complete details.
Agency Approvals:	ETL to UL 60950-1; C-ETL -US listing mark

ENTECH SIGNS - ALPHA LED
1-800-383-8163
1905 WEST ARBOR ROSE
GRAND PRAIRIE, TX 75050
WWW.ALPHA-LED.COM