

09:40

11:40

12:40

04:40

17:40

18:40

22:10

07:40

CALIFORNIA

HOUSTON

WASHINGTON, DC

AUSTRALIA

LONDON

FRANKFURT

AFGHANISTAN

HAWAII

40 CHARACTER STATIC DISPLAY OR SCROLLING

SPECIFICATIONS

EBTZ-42418-8EBB/MSB-40R2

- TYPE:** ----- DIGITAL and 15 LINE ALPHANUMERIC ER= Red EY= Yellow EG= Green EB= Blue
- DISPLAY:** ----- 4-DIGIT, 7 seg. LED, 15 LINE 5 by 7 DOT- MATRIX LED and 40 Character Messge
- CHARACTER HEIGHT:** ----- 1.8" (45.72 mm) HR / MIN 1.2" 15 line location display and Date
- VISIBILITY:** ----- 40 Ft. (12.19 METERS)
- POWER REQUIREMENTS:** -- 100-240V 50~60Hz 9A (12vdc Switching Power Supply).
- FRAME:** ----- ALUMINUM (BLACK ANODIZED FINISH)
- DIMENSIONS:** ----- 12.25" x 96.25" x 1.35"
- WEIGHT:** ----- 21.25 lbs.
- OPERATING TEMP.:** ----- -17° TO 190° F
- HUMIDITY:** ----- 0% TO 95% NON-CONDENSING
- OPERATING MODE:** ----- 27 DAY LIGHT SAVINGS, 31TIME ZONES, 10yr BACKUP WITH 1sec A YEAR ACCURACY, NON-GLARE LENS,EYELET AND SAW TOOTH SURFACE MOUNT, PC INTERFACE WITH DDS TimeNet 2.0 SOFTWARE.

ALL CLOCKS USE THE DALLAS DS32 SERIES RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY.



1 SEC A YEAR ACCURATE (TCXO)

The PC is used to set the Locations and Time. The Clock can run on its own without the PC after setting. NOTE: The colones flashing on zone 1 when it is not running on the PC.

