



SPECIFICATIONS

ENTECH SIGNS - ALPHA LED
WWW.ALPHA-LED.COM
1-800-383-8163

EBTZ-42425-6

- TYPE:** ----- DIGITAL
- DISPLAY:** ----- 4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
- CHARACTER HEIGHT:** ----- 2.5"(63.5 mm) HR./MIN. **NEW 1 SEC A YEAR ACCURATE (TCXO) STANDARD**
- VISIBILITY:** ----- 100 Ft. (30.48 METERS)
- POWER REQUIREMENTS:** 110-240V 50~60Hz (12vdc **SWITCHING POWER SUPPLY**)
- FRAME:** ----- ALUMINUM (BLACK ANODIZED FINISH)
- DIMENSIONS:** ----- 7.25" x 80.25" x 1.375"
- WEIGHT:** ----- 9.5 lbs.
- OPERATING TEMP.:** ----- -17° TO 190° F
- HUMIDITY:** ----- 0% TO 95% NON-CONDENSING
- OPERATING MODE:** ----- SYNCHRONIZED ZONES WITH ONE MASTER SET ZONE.



- 1.8", 2.5" and 4" DIGIT SIZE
- 12 OR 24 HOUR FORMAT
- 2 TO 24 ZONES
- NON GLARE LENS
- SUPER BRIGHT LEDs
- CUSTOM LETTERING TO YOUR SPECIFICATION
- ALUMINUM FRAME SURFACE MOUNT OR FLUSH
- 10 YEAR LITHIUM BATTERY BACKUP (Standard)
- AUTOMATIC DAY LIGHT CORRECTION (Standard)
- INFRARED REMOTE CONTROL (Standard)
- ONE SEC A YEAR ACCURACY (TCXO) (Standard)

