



ENTECH SIGNS - ALPHA LED
 1-800-383-8163
 WWW.ALPHA-LED.COM

EBTZ-42425-8ERY/USB



SPECIFICATIONS

- TYPE: ----- DIGITAL and DOT MATRIX LED **LOCATION** in Red, Yellow, Green or Blue
- DISPLAY: ----- 4-DIGIT, 7 seg. **TIME** in Red, Green or Blue
- CHARACTER HEIGHT: ----- 2.5" (63.5 mm) hr/min 1.2" (30.48mm) **15 character location display**
- VISIBILITY: ----- 85Ft. (25.90 METERS)
- POWER REQUIREMENTS: ---- 100-240vac 47~63Hz (12vdc Switching Power Supply)
- FRAME: ----- ALUMINUM (BLACK ANODIZED FINISH)
- DIMENSIONS: ----- 8.25" x 64.25" x 1.375" **TWO PART**
- WEIGHT: ----- 25.5 lbs.
- OPERATING TEMP.: ----- -17° TO 190° F
- HUMIDITY: ----- 0% TO 95% NON-CONDENSING
- OPERATING MODE: ----- **31 DAY LIGHT SAVINGS, 31TIME ZONES, 10yr BACKUP WITH 1sec A YEAR ACCURACY, NON-GLARE LENS, EYELET FOR SURFACE OR CEILING MOUNTING AND DDS SOFTWARE.**



1 SEC A YEAR ACCURATE (TCXO)

THE PC IS USED TO SET THE LOCATION DISPLAY AND TIME. THE CLOCK CAN RUN ON ITS OWN WITHOUT THE PC.

