



EBTZ-42440-6ER/DACY-6

SPECIFICATIONS

- TYPE:** ----- 15 Character Alphanumeric in (**RED-ER, GREEN-EG, YELLOW-EY and BLUE-EB**)
- DISPLAY:** ----- 4-DIGIT, 7 seg. LED and 15 LINE 5 by 7 DOT- MATRIX LED
- CHARACTER HEIGHT:** ----- 4" (101.6 mm) Hr / Min and 1.2" 15 line location display
- VISIBILITY:** ----- 150 Ft. (45.72 METERS)
- POWER REQUIREMENTS:** -- 100-240vac 50/60Hz (**SWITCHING TRANSFORMER**)
- FRAME:** ----- ALUMINUM (BLACK ANODIZED FINISH)
- DIMENSIONS:** ----- 13.25" x 96.25" x 1.38"
- WEIGHT:** ----- 23.5 lbs.
- OPERATING TEMP.:** ----- -17° TO 190° F
- HUMIDITY:** ----- 0% TO 95% NON-CONDENSING
- OPERATING MODE:** ----- **PC OPERATION RS485, ZONE SELECTABLE, AUTOMATIC DAY LIGHT**



NEW 1 SEC A YEAR ACCURATE (TCXO) STANDARD



THE PC IS USED TO SET THE LOCATION DISPLAY AND TIME. THE CLOCK CAN RUN ON ITS OWN WITHOUT THE PC.

100ft RS232 IF OVER THE CNV-RS232/485 CONVERTOR IS REQUIRED

